

SURESTRIP

METAL, WOOD & CONCRETE

Part Number: CCP-S112

Product Data Sheet

PAINT REMOVER SERIES



SURESTRIP is a fast-acting, flammable remover for varnish paint, synthetic enamel, lacquer and shellac. This is a watery or very liquid product that is meant to be applied on flat surfaces or in a dip tank. **SURESTRIP** will not raise the grain or discolor the finest woods. It will not be necessary to neutralize the surface with water before painting.

APPROVED SURFACES

SURESTRIP removes lacquer, enamel, vinyl, latex, varnish, acrylics, shellac and polyester finishes from the following surfaces:

- Metal
- Wood
- Concrete

THIS PRODUCT SOFTENS LINOLEUM ASPHALT, RUBBER TILE, VINYL, PLASTICS AND FIBERGLASS

DIRECTIONS:

1. Wear chemical-resistant gloves and chemical splash goggles. Shake well and open slowly to relieve pressure.
2. Pour into a metal container and apply with a paint brush to a small or large area. Brush in one direction only. Leave the area and let the stripper do the work.
3. After 15 minutes, test-scrape a small area to see if the finish is ready for removal. Remove loosened finish by scraping with a metal scraper, putty knife or brush. If you are stripping wood be sure to scrape gently in the direction of the wood grain with a plastic stripping tool. A toothbrush, toothpick, or stripping brush will help remove old finish buried in recesses. Multiple coats or stubborn finishes may require repeat applications.
4. Use a clean abrasive pad dipped in Mineral Spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before refinishing.

DIRECTIONS: DIP TANK APPLICATIONS

1. **Protect your hands with polyethylene or neoprene gloves. Open the container slowly to relieve any pressure.**
2. Pour the **SURESTRIP** into an open container. The container should be large enough to fully submerge the parts being stripped. Be sure to use metal tools to dip the parts in the tank to avoid contact with the skin. Leave the parts submerged in the stripper for 10 -15 minutes and then remove.
3. The finish should be removed using steel wool and/or a brush and water. If the finish is not entirely stripped from the part then repeat the process until the part is thoroughly stripped.
4. To Refinish: wash with water and allow to dry completely. Prepare the area that will be refinished according to the manufacturer's instructions.

HELPFUL TIPS:

Do not mix with any other product. For best results, use in temperatures between 65°F - 85°F and away from strong breeze and hot sun. **SURESTRIP** softens linoleum, plastic, rubber, asphalt tile, fiberglass or other synthetics. Use **SURESTRIP** over a small area, because health and safety risks will increase dramatically when used over a large area. If applying to a vertical surface, begin at the bottom and work up because vapors can accumulate near the floor.

CLEAN UP:

Return unused stripper to the original container. The work area and tools can be cleaned up with soap and water. Wash arms and hands with cold water and soap.

DISPOSAL:

Take outdoors and allow liquids to evaporate and residue to dry. Then dispose of it in a metal container in accordance with federal, state and local regulations.

STORAGE:

Once opened, stripper should be used within 6 months or disposed of properly to avoid deterioration of container. Store in a cool place. Exposure to high temperatures or prolonged exposure to sun may cause can to swell or leak.

DANGER - POISON!

MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. HARMFUL VAPOR. EYE & SKIN IRRITANT. USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.

Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors, open all windows and doors and maintain cross ventilation so fresh air moves across the work area. If a strong odor is noticed or you experience slight dizziness – STOP – ventilation is inadequate. Leave the area immediately.

IF WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.

A dust mask does not provide protection against vapors. Contains Methanol and Methylene Chloride. Cannot be made non-poisonous. Methylene Chloride has been shown to cause cancer in laboratory animals. The risk to health depends on the level and duration of exposure. Reports have associated repeated and prolonged overexposure to solvent with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid breathing of vapors or mist and contact with chemicals which are known to the State of California to cause cancer and reproductive harm.

FIRST AID

IF SWALLOWED, IMMEDIATELY CALL YOUR POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM OR PHYSICIAN FOR INSTRUCTIONS.

IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH WITH WATER, REMOVE ANY CONTACT LENS AND CONTINUE FLUSHING WITH WATER FOR AT LEAST 15 MINUTES, THEN GET IMMEDIATE MEDICAL ATTENTION.

IN CASE OF SKIN CONTACT, IRRITATION MAY RESULT. IMMEDIATELY WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

KEEP OUT OF REACH OF CHILDREN