COMPANY, INC.

Main Office Tel: **978 777** 7860 California Office Tel: 949 615 2939 URL: surfacelabs.us E-mail: sales@transene.com Address: 10 Electronics Avenue Danvers MA 01923

Y-SANDIT

LIQUID SANDER, REPAIR & MAINTENANCE CLEANER
Part Number: CCP-Y-SANDIT

Product Data Sheet

PAINT REMOVER SERIES



Y-sandit[™] is a solvent blend, formulated to efficiently prepare and clean surfaces that have undergone a chemical paint removal process. It functions as an alternative to rinsing with water or materials containing water. Y-sandit[™] will not cause swelling or lifting of wood grain or discoloration of wood surfaces. Use to remove paint, particulates and debris that remain bonded or clinging to the surface and/or in hardto-reach areas (such as: crevasses in carvings, filigree and intricate designs used in wood working).

APPROVED SURFACES:

y-sandit[™] removes lacquers, enamels, vinyl, latex, varnishes, acrylics and shellac finishes from the following surfaces:

- metal
- wood
- concrete

DIRECTIONS FOR USE:

- Use NIOSH approved protective equipment. Do not use in areas where vapors can accumulate – always ventilate areas where product is used. If possible, use outdoors. If swallowed, immediately call your poison control center, hospital emergency room or physician for instructions. In case of eye contact, immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention.
- 2. Pour on a rag or the surface generously. Wipe the surface with moderate pressure to remove any remaining paint and debris. Wipe in the direction of the woodgrain for best results.
- **3.** Check for remaining paint and debris. Repeat where necessary.
- **4.** Allow the surface to dry thoroughly. If needed sand lightly and repeat step 1 before refinishing.
- 5. Clean up residue, brushes and tools with mineral spirits.
- 6. Pour on a rag or the surface generously. Wipe the surface with moderate pressure in the direction of the woodgrain for best results.
- 7. Check for remaining paint and debris. Repeat where necessary.
- **8.** Allow the surface to dry thoroughly. If needed, sand lightly and repeat step 1 before refinishing.
- 9. Clean up residue, brushes and tools with mineral spirits.

KEEP OUT OF REACH OF CHILDREN